

Eveblades® Refill Instructions

WARNING!

Bending or twisting any portion of the blades may cause damage and poor wiping.

Keep wires from sharp edges in all steps.

1. Remove **black ties** securing the wires to the wiper blade structure holder by cutting them.
2. Unplug **wire connector** plugs (one on each end of individual blade = 4 connectors)
 - a. Pull the **wire connectors** apart using one hand on both ends of the connector.
 - b. *(You have to slip your fingernails under the little ears on the connectors so that they will release.)*
3. Squeeze the end of the clip (found at one end of the blade) in order to allow the clip to be pulled straight out.
4. Remove old **blade and metal strip**.
5. Insert the **metal strip on the NEW blade** onto the **blade holder** until the clip **SNAPS**.
 - a. Slide it onto one end of the blade holder and work it through all the claws that hold the metal strip in place.
 - b. The refill should not pull off once the clip **SNAPS**.
6. Reconnect each of the **4 wire connectors** (two per wiper).
7. Use the **black ties** (supplied with refills) to secure the wires to the blade structure and wiper arm.

CAUTION: Do NOT restrict the wire or the blade-action by pulling the wire taught.

If you purchase a complete blade assembly you can skip steps 1,3,4,5 and part of 7!

Instead you just remove the entire assembly from the wiper arm and replace it!

- Turn wiper heater switch ON to make sure blades heat.
 - a. If they DON'T heat — recheck your connections at all points.
 - b. If no heat in a few minutes, **check fuses** and **connections**.
 - c. Make sure both **grounds** are **GOOD**.
 - d. If they DO heat — you have been successful!
 - e. ***You could sing or hum “I Can See Clearly Now” by Johnny Nash!***
Please call us if you have any questions or problems.

Everblades® — “The Hot Ones!”

A proven produce since 1986.

W.N. Miller Company, Inc.

1-800-746-0428

www.Everblades.com

Manufactured in the Upper Peninsula of Michigan, USA